



SF21 THRU SF28

SUPER FAST RECOVERY SILICON RECTIFIER

Reverse Voltage - 50 to 600 Volts Forward Current - 2.0 Ampere

FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Super fast switching for high efficiency
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
250°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension

MECHANICAL DATA


Case: JEDEC DO-15 molded plastic body

Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.014 ounce, 0.40 grams



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for current capacitive load current derate by 20%.

Characteristic	SYMBOLS	SF21	SF22	SF23	SF24	SF25	SF26	SF28	UNITS	
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	300	400	600	V	
Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	420	V	
Maximum DC blocking voltage	V _{DC}	50	100	150	200	300	400	600	V	
Maximum average forward rectified current 0.375" (9.5mm) lead length at T _A =55°C	I _(AV)	2.0							A	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	50.0							A	
Maximum instantaneous forward voltage at 2.0A	V _F	0.95			1.25		1.7		V	
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =100°C	I _R	5.0 50.0							μA	
Maximum reverse recovery time (NOTE 1)	t _{rr}	35							ns	
Typical junction capacitance (NOTE 2)	C _J	60.0				30.0				pF
Typical thermal resistance (NOTE 3)	R _{θJA}	50.0							°C/W	
Operating junction and storage temperature range	T _J , T _{STG}	-65 to +150							°C	

Note: 1. Reverse recovery condition I_F=0.5A, I_R=1.0A, I_{rr}=0.25A

2. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

3. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted



SF21 THRU SF28

RATINGS AND CHARACTERISTIC CURVES

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE




FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE

